



## KD5065

**Switching Power Supply 91W - 12-14-15-16-18-18,5-19-19,5-20-21-22- Vdc - 6A -1XUSB 5V 2A- 10 connectors**

### Caratteristiche Generali

Technology: switching  
 Construction: desktop

### Electrical characteristics

Regulation type: CV  
 AC Input voltage: 100-240Vac  
 Frequency: 50/60Hz  
 Max input current: 1600mA  
 Insulation class: II  
 Power: 81.4W  
 Corrente d'uscita: 6000mA  
 Tensione d'uscita: 12 - 22V  
 Ripple: <250mV  
 Protections: sovraccarico, corto circuito

### Mechanical characteristics

Dimensions (LxWxH): 154.5 x 59 x 36.8mm  
 Cooling: passive  
 Protection grade: IP20  
 Housing material: Plastico  
 Color: Black  
 Connections: interchangeable connector  
 Output cable: integrato 1.6m  
 Connectors: 6,3x3,0mm, 5,5x2,5mm, 4,75x1,7mm, 7,4mm, 5,5x1,7mm, 5,5x2,1mm, 4 Pin, 5mm, 7,9mm, 6,5mm  
 Input cable: separato 1.2m da Spina Europa

### Thermal characteristics

Working temperature: 0/30°C

## Connectors





## Related Products

Code	Description
KD5065/01	Adatt. x KD5065 4,75X1,70 per Compaq/HP
KD5065/02	Adatt. x KD5065 7,40X0,60 per Dell (IC)
KD5065/03	Adatt. x KD5065 4,50X3,0 per Dell (IC)
KD5065/04	Adatt. x KD5065 4.00X1,20 per Asus
KD5065/05	Adatt. x KD5065 5,50X2,50 per Panasonic
KD5065/06	Adatt. x KD5065 4,00X1,70 per HP