



IDEAL APPLICATIONS

Advanced gaming High-resolution multimedia systems Overclocked water-cooled systems

HIGHLIGHTS

Doubly decoupled PWM pump Light Wings PWM high-speed fan for highest performance and silent operation Unmistakable design with ARGB lighting and aluminum-style cooling block Easy-to-access refill port

Impressive illumination, superior cooling

Pure Loop 2 FX is the very high performing and silent All-in-One water cooling unit with impressive illumination for slightly overclocked systems.

Highlights

- High cooling performance
- Up to 3 Light Wings PWM high-speed fans offer equally high air pressure and vibrant illumination
- Doubly decoupled PWM pump for quiet operation and minimal vibration
- ARGB-PWM-Hub enables synchronization of up to 6 ARGB components and PWM fans
- Combination of ARGB illumination, all-black design and aluminum-style for unmistakable and stylish look
- Easy-to-access refill port and included coolant bottle guarantee a long lifespan
- Nickel-coated coldplate allows optimum use of liquid metal thermal compound
- 3-year manufacturer's warranty
- Product conception, design and quality control in Germany



PURE LOOP 2 FX

General Data			
Model	360mm	280mm	240mm
Article no.	BW015	BW014	BW013
EAN code	4260052189047	4260052189030	4260052189023
Dimensions radiator, incl. fan (H x W x D), (mm)	397 x 120 x 52	317 x 140 x 52	277 x 120 x 52
Total weight (g)	1545	1290	1180
Socket compatibility	Intel: 1700 / 1200 / 2066 / 1150 / 1151 / 1155 / 2011(-3) Square ILM AMD: AM5 / AM4		
Noise level (dB(A)) @ 25 % / 50% /100% rpm	8.9 / 20.1 / 34	10.8 / 22.4 / 32.8	8 / 16.7 / 32.3
Pump speed max. (rpm)	5500		
Pump operation range (rpm)	4000 - 5500		
Pump connector	4-pin PWM		
Refill port	•		
Radiator specification			
Dimensions (H x W x D), (mm)	397 x 120 x 27	317 x 140 x 27	277 x 120 x 27
Radiator material / finish	aluminum / black spray painted		
Base material / finish	copper / nickle plating		
be quiet! Light Wings fans			
Fan dimensions (mm) / Quantity (pcs.)	120 x 120 x 25 / 3	140 x 140 x 25 / 2	120 x 120 x 25 / 2
Speed @ 100% PWM (rpm)	2500	2200	2500
Input current (A)	0.45	0.39	0.45
Connector	4-pin PWM		
Lifespan (h / 25°C)	60,000		

Logistics data			
Pure Loop 2 FX	Article no	EAN code	
360mm	BW015	4260052189047	
280mm	BW014	4260052189030	
240mm	BW013	4260052189023	



Contact			
be quiet! headquarters	Service hotline: +49 40 7367 686 44		
Listan GmbH Wilhelm-Bergner-Straße 11c 21509 Glinde Germany	e-mail: service@bequiet.com Visit the contact section on bequiet.com for the right regional service information.		