BOOST YOUR BUSINESS PRODUCTIVITY WITH FAST AND EFFICIENT MULTI-FUNCTIONAL BLACK AND WHITE LASER PRINTERS



i-SENSYS MF450 series

Designed for small to medium businesses or individuals working remotely, the Canon i-SENSYS MF450 Series is compact, efficient, and productive.



Cloud connectivity

Print or scan from the cloud, with one -touch built-in connectivity to cloud storage services, including Google Drive, DropBox, and OneDrive.

Mobile printing

Conveniently print documents from your from smartphone or tablet with the Canon PRINT Business app, or via AirPrint (iOS) and Mopria (Android).

Reliable security

Protect your documents with Secure PIN functionality, which restricts printing of sensitive documents, and avoid hacking or virus threats with Verify System at Startup.

Superior efficiency

Super-fast print speeds, double-sided single-pass scanning and double-sided printing as standard ensure ultimate productivity.

Customised workflows

Automate everyday tasks such as printing stored forms, scanning to email, and copying documents with on-screen buttons and Canon's Application Library.







MF453dw

MF455dw

Fax		•
A4 print speed	38ppm	38ppm
Display	12.7cm colour touch screen	12.7cm colour touch screen
Secure PIN print	•	•
Duplex printing	•	•
Built-in cloud connectivity	•	•
Application Library	•	•
Single Pass Duplex Scan		•
Wireless connectivity	•	•



TECHNICAL SPECIFICATIONS

i-SENSYS MF450 series

1achine type	Mono Laser All-In-One	Media weights	Cassette (standard and optional): 60 to 120 g/m ²		
vailable functions	MF455dw: Print, Copy, Scan and Fax	riould noighto	Multi-purpose tray: 60 to 163 g/m ² ADF: 50 to 105 g/m ²		
	MF453dw: Print, Copy and Scan	Double sided printing	A ⁴ , Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Fools Custom size - Min. 210 x 279.4 mm Max. 216.0 x 355.6 mm		
RINTER int speed	Single sided : Up to 38 ppm (A4)		60 to 120 g/m ²		
int speed	Up to 63.1 ppm(A5-Landscape)	INTERFACE & SOFTWARE			
inting method	Double sided : Up to 31.9 ipm (A4) Monochrome laser beam printing	Interface type	USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireles		
int resolution	Up to 1200 x 1200 dpi		802.11b/g/n, Wireless Direct Connection		
arm-up time	Approx. 14 seconds or less from power on	Operating System compatibility	Windows* 11 / Windows* 10 / Windows* 8.1 / Server* 2019 / Server* 2016 / Server* 2012R2 / Server* 2012 /		
rst Print Out Time	Approx: 5.5 seconds or less		Server* 2008R2 / Server* 2008 Mac OS X version 10.11 & up		
inter languages	UFRII, PCL 5e ² , PCL6, Adobe* PostScript ³		Linux ⁵		
onts	45 PCL fonts	Network Protocol	Print:		
int marging	136 PostScript fonts 5 mm-top, bottom, left and right		TCP/IP (LPD/Port9100/IPP/IPPS/WSD) Scan:		
int margins	10 mm-top, bottom, left and right (Envelope)		Push Scan: File: FTP (TCP/IP), SMB3.0 (TCP/IP) E-mail/I-Fax: SMTP (send), POP3 (receive)		
oner saver mode dvanced printing features	Yes Secure Print		Pull Scan: TCP/IP		
avanced printing reatures	Print from USB memory key (JPEG/TIFF/PDF) Print from Cloud ¹ (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG)		Management: SNMPv1, SNMPv3 (IPv4,IPv6)		
	iOS: AirPrint, Canon PRINT Business app				
	Android; Mopria certified, Canon PRINT Business app, Canon Print Service Plug-in		Security: TLS1.3, IPSec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)		
	Service Flug-III		Security (wireless): Infrastructure Mode:		
OPIER			WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES)		
opy speed	Single sided (A4): Up to 38 ppm Double sided (A4): Up to 30.3 ipm		Access Point Mode: WPA2-PSK(AES)		
rst Copy Output Time	ADF (A4): Approx. 6.6 seconds or less	Software and printer	MF Scan Utility,		
COT)	Platen (A4): Approx. 6.4 seconds or less	management	Remote User Interface (RUI), Department ID Management,		
opy resolution	Up to 600 x 600 dpi		Toner Status Tool,		
opy modes	Text, Text/Photo (Default),Text/Photo (High Quality), Photo		iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices		
ouble sided copying	2-sided to 2-sided (Automatic)		eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management an		
ultiple copy eduction / Enlargement	Up to 999 copies 25-400% in 1% increments		remote diagnostics		
ther features	Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy		Application Library		
		GENERAL FEATURES			
PPE PPE	Colour	Recommended Monthly Print Volume	750 - 4,000 pages per month		
an resolution	Optical: Up to 600 x 600 dpi	Duty cycle	Max. 80,000 pages per month ⁶		
	Enhanced: Up to 9600 x 9600 dpi	Processor Speed	800MHz x 2		
can speed	Single sided mono: 38ipm (300x600dpi) Single sided colour: 13ipm (300x600dpi)	Memory	1GB		
	Double sided mono: 70ipm (300x600dpi) Double sided colour: 26ipm (300x600dpi)	Control panel	12.7 cm LCD Colour Touch Screen		
olour scanning depth	24 bit/24 bit (input/output)	Dimensions with trays	453 mm x 464 mm x 392 mm		
reyscales	256 levels	(W x D x H)	682 mm x 1,083 mm x 895 mm		
ompatibility	TWAIN , WIA, ICA	Installation space (W x D x H)	662 mm x 1,065 mm x 695 mm		
ax. scan width	216mm	Weight	Approx. 17.2 Kg		
can to E-mail	TIFF/JPEG/PDF/Compact PDF/Searchable PDF	Operating environment	Temperature: 10 to 30°C (50 to 86°F)		
can to PC			Humidity: 20 to 80% RH (no condensation)		
can to USB memory key		Power Source	220-240V(±10%) 50/60Hz (±2Hz) Maximum: Approx. 1,370 W		
can to FTP can to Cloud ¹	TIFF/JPEG/PDF/PNG ³	Power Consumption	Standby: Approx. 9.4 W		
AX	ITU-T.37		Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 0.33 kWh/week		
			(230V) ¹¹		
AX .	MF455dw ONLY		For detailed information relating to Lot26 regulation, pleas go to: http://www.canon-europe.com/For Work/Lot26/		
odem speed	33.6 Kbps (Up to 3 seconds/page ⁴)		index.aspx		
eceive mode ax resolution	Fax only, Fax/Tel Auto Switch, Answer Mode, Manual Standard: 200 x 100 dpi	Noise Levels	Sound Pressure ⁷ :		
	Fine: 200 x 200 dpi		Active: 53 dB Standby: Inaudible [®]		
	Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi				
AX memory	Up to 512 pages ⁴		Sound Power ⁷ : Active: 72.2 dB		
peed dials	Up to 281 dials		Standby: Inaudible [®]		
oup dials/destinations	Max. 299 dials / Max. 299 destinations	CONSUMABLES			
equential broadcast	Max. 310 destinations	Cartridges	Cartridge 057 (3,100 pages ⁹) ¹⁰		
emory backup	Permanent fax memory backup (Backup with flash memory)		Cartridge 057H (10,000 pages ⁹) ¹⁰		
ouble sided faxing ther features	Yes (Transmit and Receive) Sender's Name (TTI), Direct Send, TX Report, Sequential	ACCESSORIES/ OPTIONS			
	Broadcasting	ltems	MF455dw:		
EDIA HANDLING			CST.Feeding Module-AH1 (550-sheet cassette)		
canner type	Platen, 2-sided ADF (single pass)		TEL 6 Kit Long Cord (Telephone handset) MF453dw:		
aper input (Standard)	250-sheet cassette 100-sheet multi-purpose tray		CST.Feeding Module-AH1 (550-sheet cassette)		
	50-sheet ADF	Notes:			
per input (Option)	550-sheet cassette 150-sheet		y cloud service is required, and subject to their party terms and		
iper output edia types	150-sheet Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post		conditions.		
	card, Envelope	 A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device. Scan by ME Scan Utility or Canon PPINT Business 			
edia sizes	Cassette (Standard and optional):				
	A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K,	 ⁽⁴⁾ Based on ITU-T Standard Chart No. 1 ⁽⁵⁾ Linux support both printing and scanning 			
	Custom sizes: Min. 105 x 148 mm Max. 216.0 x 355.6 mm.	[6] Duty cycle is defined as the	maximum number of printed pages for a single peak month. Any usa		
	Multi-purpose tray:		uty cycle may decrease the life of the product		
	A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K,	^[7] Declared noise emission in accordance with ISO 9296			
	Indexcard, Envelope (COM10, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 216.0 x 355.6 mm.	 Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779 Based on ISO/IEC 19752 			
		^[10] Printer ships with Cartridge 057 (3,100 pages)			
	ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 105 x 128	^[10] Printer ships with Cartridge	057 (3,100 pages)		





PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS MF453dw	5161C014BA	8714574670393
i-SENSYS MF455dw	5161C017BA	8714574670423

ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
Cassette Feeding Module-AH1	0732A033AA	4549292092769
Telephone 6 Kit EU (CW)	0752A054AA	4960999453910
- Telephone 6 Kit UK (CW)	0752A053AA	4960999453897
Telephone 6 Kit SA (CW)	0752A055AA	4960999453927

CONSUMABLES:

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 057	3009C002AA	4549292136258
Cartridge 057 H	3010C002AA	4549292136289

Canon Ireland

3006 Lake Drive Citywest, Saggart Co. Dublin, Ireland Telephone No: 01 2052400 Facsimile No: 01 2052525 canon.ie

Canon (UK) Ltd 5 The Square Stockley Park Uxbridge UB11 1ET Tel: 01895 648 000 www.canon.co.uk

Canon Inc. canon.com Canon Europe canon-europe.com English edition © Canon Europa N.V.,2021

