

# Access Points Tech Specs

---

## In the Box

- Meraki Go Indoor WiFi Access Point - GR10; OR
- Meraki Go Outdoor WiFi Access Point - GR60
- Quick start guide
- Wall mount and screw kit
- Power supply - US/UK/EU depending on region
- Ethernet cable

---

## Radios

- 2.4 Ghz 802.11b/g/n client access radio
- 5 Ghz 802.11a/n/ac client access radio
- 2 x 2 MIMO with two spatial streams

---

## Interfaces

- 1x 10/100/1000 BASE-T Ethernet (RJ45)
- 1x DC power connector (5.5 mm x 2.5 mm, center positive)

---

## Physical Specifications

### **INDOOR ACCESS POINT**

- 7.95" x 4.8" x 1" (202 mm x 123 mm x 26 mm), not including mount
- 9.6 oz (272 g)

- Operating temperature: 32°F to 104°F (0°C to 40°C)
  - Humidity: 5 to 95% non-condensing
- 

#### **OUTDOOR ACCESS POINT**

- 9.56" x 4.48" x 1.18" (243 mm x 114 mm x 30 mm), not including desk mount feet or mount
  - 15.87 oz (0.45 kg)
  - Operating temperature: 32°F to 122°F (0°C to 50°C)
  - Humidity: 5 to 95% non-condensing
  - IP67 environmental rating
- 

## Power

- Power over Ethernet: 37–57 V (802.3af compatible)
  - Alternative 12 V DC input
  - Power consumption: 11W max (802.3af)
- 

## Antenna

Integrated omni-directional antennas

#### **INDOOR ACCESS POINT**

- 5.6 dBi gain at 2.4 GHz, 5.3 dBi gain at 5 GHz
-

---

#### **OUTDOOR ACCESS POINT**

- 4.5 dBi gain at 2.4 GHz, 4.7 dBi gain at 5 GHz

---

#### Warranty

- 1-year hardware warranty

---

#### Model List

- Indoor Access Point - GR10-HW-XX
- Outdoor Access Point - GR60-HW-XX
- XX = US/UK/EU Power

---

#### Accessories

- Spare Power Adapter for WiFi Access Point (US) - GA-PWR-12W-US
  - Spare Power Adapter for WiFi Access Point (UK) - GA-PWR-12W-UK
  - Spare Power Adapter for WiFi Access Point (EU) - GA-PWR-12W-EU
  - Spare Mount Plate for Indoor WiFi Access Point - GA-MNT-GR-1
  - Spare Mount Plate for Outdoor WiFi Access Point - GA-MNT-GR-2
-