

DisplayPort™ to VGA Cable M/M 2m/6.56ft 28AWG



FULL HD
1080

Product Name:

DisplayPort™ to VGA Cable M/M 2m/6.56ft 28AWG

Product Series:

Cable

Product Code:

CAC-1012

EAN code:

8719214472207

UPC code:

841615102440

Description:

The Club 3D CAC-1012 DisplayPort™ to VGA Cable M/M 2m/6.56ft 28AWG links any DisplayPort™-equipped desktop, laptop or adapter to a monitor, display, beamer or projector with a 15-pin VGA Female port. Ideal for at home or work, the cable creates a reliable connection for anything from gaming to video projection and supports up to Full HD 1080p(max. resolution of 1920 x 1080). A Micro USB port is also provide for External Power. This quality DisplayPort™ to VGA cable provides superior performance thanks to the combined effect of its Gold plated connectors and 28 AWG conductors. Internal shielding provides reduced crosstalk, suppresses noise, and helps prevent electromagnetic interference (EMI) and radio frequency interference (RFI). Experience a reliable, high-quality connection with this convenient DisplayPort™ to VGA 2m/6.56ft cable.

Features:

- Standard DisplayPort™ Male to 15-pin VGA Male cable
- No External Power needed
- Gold-plated connectors
- Shielded for EMI/RFI interference
- Resolution up to 1920 x 1080 (Full HD 1080p)



OS Support:

- All

In the box:

- CAC-1012

Available Interfaces

Input:

- DisplayPort™ Male

Output:

- VGA Male

Other info:

- Box size: 14.5 x 14.5 x 4.5 cm / 5.71 x 5.71 x 1.77"
- Cable length: 2m/6.56ft
- DisplayPort™ Connector dimensions: 4.7 x 2 x 1.3cm / 1.85 x 0.79 x 0.51"
- VGA Connector dimensions: 4.4 x 3.3 x 1.6 cm / 1.73 x 1.3 x 0.63"
- Cable Weight: 98 gr / 3.46 oz
- Box Weight: 45 gr / 1.59 oz
- Total Weight: 143 gr / 5.05 oz
- Meets ROHS, FCC, and CE EMI requirements

Please use one of our Extension/Adapter cables to connect to your devices: In case you need assistance to choose the correct cable, please visit our website www.club-3d.com or feel free to mail us at support@club-3d.com and it will be our pleasure to assist you.

Input:



Output:

