



# Delock Active DisplayPort 1.4 to HDMI Adapter 4K 60 Hz (HDR)

# Description

This adapter by Delock enables the connection of an HDMI monitor to the system via a free DisplayPort interface. The adapter supports a resolution up to 4K Ultra HD at 60 Hz and is backward compatible to Full-HD 1080p.

## **Active adapter**

The adapter offers an active conversion, thus it is also suitable for graphics cards that are not capable of outputting DP++ signals.



22 cm

#### **Specification**

- Connectors:
- 1 x DisplayPort male >
- 1 x HDMI-A female
- Chipset: Parade PS186
- DisplayPort 1.4 and High Speed HDMI specification
- Active converter, for graphics cards with DP and DP++ output
- Signal direction: DisplayPort input > HDMI output
- · Cable gauge:
- 32 AWG data line
- 28 AWG power line
- Cable diameter: ca. 5 mm
- Connectors: gold-plated
- · Metal housing
- Transmission of audio and video signals
- Data transfer rate up to 18 Gbps
- Resolution up to 3840 x 2160 @ 60 Hz

(depending on the system and the connected hardware)

- Supports HDR
- Supports HDCP 1.4 and 2.3
- 1 x ferrite core
- Cable length without connectors: ca. 20 cm
- · Colour: grey / black

#### System requirements

· A free DisplayPort female

### Package content

Adapter DisplayPort to HDMI

#### **Images**



#### Item no. 66436

EAN: 4043619664368

Country of origin: China

Package: • Retail Box







| General                    |                      |
|----------------------------|----------------------|
| Specification:             | High Speed HDMI      |
|                            | DisplayPort 1.4      |
|                            | HDR                  |
| Interface                  |                      |
| Connector 1:               | 1 x DisplayPort male |
| Connector 2:               | 1 x HDMI-A female    |
| Technical characteristics  |                      |
| Chipset:                   | Parade PS186         |
| Data transfer rate:        | up to 18 Gb/s        |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz  |
| Physical characteristics   |                      |
| Ferrite core:              | 1 x                  |
| Cable length:              | 20 cm                |
| Pin finishing:             | gold-plated          |
| Conductor gauge:           | 32 AWG data line     |
|                            | 28 AWG power line    |
| Colour:                    | grey / black         |
| Cable diameter:            | 5 mm                 |