

Delock Cable mini DisplayPort 1.1 male > HDMI-A male 0,5 m

Description

This cable by Delock can be used to connect a display with an HDMI port to a PC or a laptop with mini DisplayPort interface.



ca. 0,5 m

Specification

- Connectors:
 - 1 x mini DisplayPort 20 pin male >
 - 1 x High Speed HDMI-A 19 pin male
- Chipset: Parade PS8121E
- DisplayPort 1.1a and High Speed HDMI specification
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Signal direction: mini DisplayPort input > HDMI output
- Cable gauge: 32 AWG
- Cable diameter: ca. 5.5 mm
- Twisted-pair cabling
- Copper conductor
- Gold-plated connectors
- Triple shielded cable
- Transfer of audio and video signals
- Data transfer rate up to 10.2 Gb/s
- Resolution up to 1920 x 1200 @ 60 Hz (depending on the system and the connected hardware)
- Colour: white
- Length incl. connectors: ca. 0.5 m

System requirements

- One free mini DisplayPort DP++ female

Package content

- Mini DisplayPort to HDMI cable

Item no. 83993

EAN: 4043619839933

Country of origin: China

Package: Poly bag



Images



| | |
|----------------------------------|-----------------------------------------------------------------------|
| General | |
| Specification: | DisplayPort 1.1 High Speed HDMI |
| Interface | |
| connector: | 1 x mini DisplayPort 20 pin male 1 x High Speed HDMI-A 19 pin male |
| Technical characteristics | |
| Data transfer rate: | 10.2 Gb/s |
| Maximum screen resolution: | 1920 x 1200 @ 60 Hz |
| Physical characteristics | |
| Cable colour: | white |
| Cable diameter: | 5.5 mm |
| Cable length incl. connector: | 0.5 m |
| Connector finishing: | gold-plated |
| Pin finishing: | gold-plated |
| Conductor material: | copper |
| Conductor gauge: | 32 AWG |
| Shielding: | triple |