

Product details CFT-750-14C

With an **extreme silent 14cm fan** and the **environmental conscious 80+ efficiency features**, which fulfil the latest high-end standard. The easy-to-handle **'cable management'** ensures that no unnecessary cables disturb the optimal air circulation within a chassis. This series is not only a Gamer's dream...



zoom

Highlights:

- PS2 Form factor
- 750 Watt Intel / AMD
- EPS 12V for Dual Processor Mainboards
- ATX 2.3 Specification
- **Cable management**
- All cables in 'net tube'
- 140mm **silent fan** 25-39 dB
- 'full range' input
- active PFC (Power Factor Correction)
- AFC (Automatic Fanspeed Control)
- OVP (Over Voltage Protection)
- OCP (Over Current Protection)
- OTP (Over Temperature Protection)
- 2x 6-pin + 2 x 8(6+1)-pin Express connectors for all powerful graphic cards (SLI / Crossfire)
- **>80% Efficiency**



Technical data


Specification:

AC Input:	100V - 120V 10A 220V - 240V 5A	Voltage:	+5V	+3,3V	+12V1	+12V2	+12V3	+12V4	-12V	+5VSB
Frequency:	47-63 Hz	Current:	28A	30A	18A	18A	18A	18A	0.8A	3A
			180W MAX.		720 W MAX.				9,6W	15W
MAX. LOAD:	750W	Combined Load:								

Dimension:

15,4 cm x 15 cm x 8,5 cm (TxBxH)

Security:



Fixed cables:

Connector:				
Description:	20/24 Pin ATX	4 Pin P IV	8 Pin PCIe (6+2)	6 Pin PCIe
Q'ty:	1	1	1	1

Modular cables:

Connector:						
Description:	6 Pin PCIe	8 Pin PCIe (6+2)	PATA	Floppy	SATA	8 Pin EPS12V (4+4)

Q'ty:

1

1

6

2

4

1

