

# HP USB -C™ Adapters



## HP 45W USB-C™ AC Adapter



### Easy AC charging through USB-C™

Easily enable reliable connectivity through wired USB 3.0, Ethernet, and USB-C™ power-in connections with the HP USB-C™ to RJ45/USB3/USB-C™ Adapter.

### Simple to use

Connect one end of the adapter to the USB-C™ port on your device<sup>1</sup>, and plug the AC head into any available wall outlet.

### World-class support

Rest easy with a one-year parts replacement limited warranty.

## HP USB-C™ to USB 3.0 Adapter

### Enable easy device connectivity

Convert your notebook or tablet's USB-C™ port to USB 3.0 with the HP USB-C™ to USB 3.0 Adapter.

### Simple to use

Use the adapter to connect to your frequently-used USB 3.0 devices through your notebook or tablet's USB-C™ port.

### World-class support

Rest easy with a one-year parts replacement limited warranty.



<sup>1</sup>See product QuickSpecs for exact compatibility.

## HP USB-C™ to RJ45/USB3/USB-C™ Adapter



### Be more productive

Easily enable reliable connectivity through wired USB 3.0, Ethernet, and USB-C™ power-in connections with the HP USB-C™ to RJ45/USB3/USB-C™ Adapter.

### Get online

Use the adapter to convert your USB-C™ port to a wired Ethernet connection and reliably access secure corporate networks or other Internet connections where wireless is spotty or unavailable (Ethernet cable required).

### Charge it up

Connect to your wired USB 3.0 peripherals and power your device with the convenient USB-C™ power in connector at the same time.

### World-class support

Rest easy with a one-year parts replacement limited warranty.

## HP USB-C™ to 3 and 4.5 mm Adapter

### Power up with added simplicity

Travel light with the HP USB-C™ to 3 and 4.5 mm Adapter, which lets you use one power adapter to charge your tablet and notebook.<sup>1</sup>

### Easy to use

Connect one end of the adapter to the USB-C™ port on your tablet or notebook<sup>1</sup>, and on the other end, connect your HP Smart AC Adapter up to 60W.

### World-class support

Rest easy with a one-year parts replacement limited warranty.



<sup>1</sup>See product QuickSpecs for exact compatibility.


## Specifications



	<b>HP USB-C™ to RJ45/USB3/USB-C™ Adapter</b>	<b>HP USB-C™ to USB 3.0 Adapter</b>	<b>HP USB-C™ to 3 and 4.5 mm Adapter</b>	<b>HP USB-C™ to RJ45 Adapter</b>
<b>Part number</b>	N2Z64AA	N2Z63AA	N2Z65AA	V7W66AA
<b>Dimensions</b>	7.12 x 2.80 x 0.74 in (18.07 x 7.10 x 1.87 cm)	5.55 x 0.92 x 0.43 in (14.08 X 2.33 X 1.10 cm)	6.32 x 1.87 x .75 in (16.06 x 4.75 x 1.90 cm)	7.1 x 0.8 x 0.7 in (18.0 X 2.1 x 1.7 cm)
<b>Weight</b>	8.64 ounces (245 g)	.71 ounces (20 g)	1.76 ounces (50 g)	2.5 ounces (71.4 g)
<b>Connectors</b>	USB-C to RJ45/USB 3/USB-C	USB-C to USB 3.0 Adapter	3mm DC jack, 4.5mm DC jack, and USB-C	1 x 22 pin USB Type C
<b>LEDs</b>	Network connection indicators	None	None	Yes
<b>Environmental Design</b>	Operating Temperature: 0°C to 40°C Non-operating (storage) -20°C to 60°C Humidity: 20%-80% RH Storage Humidity: 20%-90%RH EMI and Safety Certifications: CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/UL&cUL/KCC/EAC/UK/SABS&NRCS/CB	Operating Temperature: 0°C to 40°C Non-operating (storage) -20°C to 60°C Humidity: 20%-80% RH Storage Humidity: 20%-90%RH EMI and Safety Certifications: CE/FCC&IC/BSMI/VCCI/C-tick(RCM)/UL&cUL	Operating Temperature: 0°C to 40°C Non-operating (storage) -40 to +70 °C Humidity: 50% RH	Operating Temperature: 0C to 70C Non-operating (storage): -55C to +125C Humidity: Level 3 Storage Humidity: <=90% RH in Al bag EMI and Safety Certifications: EMC, CB, VCCI, CE, REACH, FCC, RCM, KCC, EAC, Ukraine
<b>Compatible Operating Systems:</b>	Windows 10 (32-bit and 64-bit), Windows 8 (32-bit and 64-bit), Windows 7 (32-bit and 64-bit), and Chrome			

**Sign up for updates**  
[hp.com/go/getupdated](http://hp.com/go/getupdated)

     
Share with colleagues

  
Rate this document

© Copyright 2015-2016 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. All other trademarks are the property of their respective owners.

4AA6-1058ENW, February 2016, Rev 1.

