


IB-DK2254AC
Order Number **EAN Number**
 60802 4250078171386

USB Type-C® & Type-A DockingStation with triple video output

From a good DockingStation we expect connectivity, reliable performance, good design and advanced technology. With the IB-DK2254AC, these expectations are fulfilled. Our DockingStation is extremely versatile and creates a full-fledged workstation at home or in the office. The IB-DK2254AC supports both DisplayLink® and DisplayPort™ Alt Mode. This allows you to connect three additional monitors and expand the visible screen area. With a resolution of up to 3x 4K or 1x 5K, you can work even more effectively as annoying switching between programmes is reduced. There are also six USB 3.0 Type-A ports for your peripherals and a 3.5 mm combo jack for the headset. Power Delivery with up to 100 W is supported via the host connection. So you can charge your notebook or MacBook while you're at it.


Host

 Supports
 USB Type-A,
 USB Type-C®

Multiple Display

Supports 3x up to 4K@60 Hz


USB

 6x USB 3.0 Type-A
 up to 5 Gbit/s

Headset

3.5 mm combo jack


LAN Port

 RJ 45
 Gigabit Ethernet


DisplayLink®

 Driver installation required
 before first use:
www.displaylink.com/downloads

FRONT VIEW



REAR VIEW



SPECIAL FEATURES




6x USB Type-A for absolute flexibility

The IB-DK2254AC DockingStation turns your notebook into a fully-fledged workstation. Simply connect the DockingStation to your notebook via USB Type-A or USB Type-C®. You have 6x USB 3.0 Type-A with up to 5 Gbit/s at your disposal, enabling you to connect hard drives and other devices.



See more, work efficiently

The ICY BOX® DockingStation supports both DisplayLink® and DisplayPort™ Alt Mode. This allows you to connect three additional monitors and expand the visible screen area. With a resolution of up to 3x 4K@60 Hz, you can work even more effectively because annoying switching between programmes is reduced.



Always well connected

You can establish a fast and secure network connection via the Gigabit Ethernet connection of the DockingStation. This means you are independent of WLAN reception. For undisturbed video conferencing, just connect your headset to a 3.5 mm combo jack. Of course, you can also simply listen to your favourite music.

PACKING CONTENT

- ▶ 1 x IB-DK2254AC
- ▶ 1 x external power supply
- ▶ 1 x power cord with EU plug
- ▶ 1 x USB Type-C® to Type-C®/Type-A cable
- ▶ 1 x manual

PRODUCT FEATURES

Colour	Material	UASP support	LED	Cooling	Power supply
Black	Plastic	Yes	Power	Passive	External power supply AC 100-240 V; 50/60 Hz; DC 20 V/6.75 A; 135 W

VIDEO CONNECTION AND DISPLAY OUTPUT MATRIX

Video matrix design (USB Type-C® DP Alt Mode + DisplayLink®, DP 1.4 HBR3), maximum resolutions						
Number of displays	INPUTS (PLUG-IN)			OUTPUT		
	Display 1	Display 2	Display 3	Display 1	Display 2	Display 3
Triple video output	✓	✓	✓	3840x2160@60 Hz	3840x2160@60 Hz	3840x2160@60 Hz
Dual video output	✓	✓		3840x2160@60 Hz	3840x2160@60 Hz	
		✓	✓		3840x2160@60 Hz	3840x2160@60 Hz
	✓		✓	3840x2160@60 Hz		3840x2160@60 Hz
	✓		✓	3840x2160@60 Hz	5120x2880@60 Hz	
Single video output	✓			3840x2160@60 Hz		
		✓			3840x2160@60 Hz	
			✓			3840x2160@60 Hz

Video matrix design (USB 3.0 DisplayLink®, only Display 2 and Display 3), maximum resolutions						
Number of displays	INPUTS (PLUG-IN)			OUTPUT		
	Display 1	Display 2	Display 3	Display 1	Display 2	Display 3
Dual video output		✓	✓		3840x2160@60 Hz	3840x2160@60 Hz
Single video output		✓			3840x2160@60 Hz	
			✓			3840x2160@60 Hz
			✓		5120x2880@60 Hz	

SYSTEM REQUIREMENTS

Supported Operating Systems	Host compatibility
Windows®/macOS®/Chrome OS™	USB 3.0 Type-A, USB Type-C®, Thunderbolt™ 3/4 Type-C®

CONNECTION TO HOST

Port	Position	Version & transfer rate	Features
1x USB Type-C® (to USB Type-A/Type-C®)	Rear	USB 3.1 (Gen 2) (10 Gbit/s)	USB data transfer, Power Delivery, DP Alt Mode

USB CONNECTIONS

Port	Position	Version & Transferrate	Voltage	Current	Power
2x USB Type-A	Front	USB 3.0 (5 Gbit/s)	5 V	900 mA	4.5 watts
4x USB Type-A	Rear	USB 3.0 (5 Gbit/s)	5 V	900 mA	4.5 watts

OTHER I/O PORTS

Port	Position	Features
Audio in/out	Front	3.5 mm TRRS speaker/microphone combo jack
RJ45	Rear	10/100/1000 BASE-T Gigabit Ethernet

SECURITY

Kensington-Security-Slot™

LOGISTICAL DATA

Packing unit	Total weight	Gross weight	Net weight	Dimension/carton	Dimension/article	Country of origin
4 Stck./Karton	5.5 kg/Karton	1.218 kg	0.287 kg	250x360x185 mm	85x230x150 mm	Thailand

DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

DisplayLink® is the registered trademark of DisplayLink Corp. in the EU, the US, and other countries.

The terms HDMI® and HDMI® High-Definition Multimedia Interface, and the HDMI® logo are trademarks or registered trademarks of HDMI® LA, Inc. in the United States and other countries.

Apple and macOS, MAC, iTunes and Macintosh are registered trademarks of Apple Computer Inc.

Microsoft, Windows and the Windows logo are registered trademarks of Microsoft Corporation.

USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum.

Chrome OS is a trademark of Google Inc. Use of this trademark is subject to Google Permissions.

All other trademarks and brand names are the Property of their respective owners.