



Intel® Solid-State Drive Data Center S3610 Series Non-Volatile Memory Storage Solutions

PRODUCT BRIEF

Consistently Amazing

The Intel® Solid-State Drive Data Center Family for SATA expands with the Intel® SSD DC S3610 Series. The Intel SSD DC S3610 Series offers the next generation of data center SSDs optimized for mixed read-write performance, endurance and strong data protection.



Proven Data Center Endurance

In today's demanding data center environments, IT needs highly reliable, fast storage coupled with consistent performance. The Intel® SSD DC S3610 Series is designed to meet the needs of typical data center workloads with up to 3 full drives writes per day, delivering up to 10 times higher endurance than standard read-optimized data center SSDs.¹ The Intel SSD DC S3610 Series is the perfect choice for applications demanding a balance of read and write performance such as operational and analytical databases, virtualization, e-commerce and cloud infrastructures.

Stress-Free Data Protection

The Intel SSD DC S3610 Series protects data with full end-to-end data protection, 256-bit encryption Advanced Encryption Standard (AES) technology, sophisticated error protection schemes, and enhanced power loss and thermal monitoring features. The Intel SSD DC S3610 Series employs multiple safeguard mechanisms delivering peace of mind that data is safe, secure and available when needed.

Power-Efficient Performance

The Intel SSD DC S3610 Series accelerates data center performance with read-write throughput speeds up to 550/520² megabytes per second (MB/s) and 4K random read-write input/output operations per second (IOPs) up to 84,000/28,000². Applications benefit from 55 μ s typical latency with max read latencies³ of 500 μ s 99.9%⁴ of the time. Combining performance with low typical active power (less than 6.8 watts^{2,5}) the Intel SSD DC S3610 Series improves data center efficiency with superior quality of service and reduced energy costs.

Exceptional Quality and Reliability

Intel® SSDs are known industry wide for their quality and reliability. The Intel SSD DC S3610 Series is no exception. The Intel SSD DC S3610 Series is engineered to reduce downtime as a result of storage-related failures. Designed to meet an Annualized Failure Rate (AFR) of 0.44%, the Intel SSD DC S3610 Series significantly reduces Total Cost of Ownership (TCO)⁶. Held to the highest standards, the Intel SSD DC S3610 Series is validated in more than 5,000 unique tests to ensure performance over the life of the drive. The Intel SSD DC S3610 Series is fully supported with Intel's 5-year limited warranty and customer support.

Capacity and Form Factors⁷

The Intel SSD DC S3610 Series is available in a 2.5-inch form factor with capacities from 200GB to 1.6TB and in a 1.8-inch form factor with capacities from 200GB to 800GB.

Intel® Solid-State Drive Data Center S3610 Series

Technical Specifications²

Model Name	Intel® Solid-State Drive DC S3610 Series	
Capacity ⁷	2.5-inch – 200GB, 400GB, 480GB, 800GB, 1.2TB, 1.6TB	
	1.8-inch – 200GB, 400GB, 800GB	
NAND Flash Memory	20nm NAND Flash Memory Multi-Level Cell Compute-Quality Components with High Endurance Technology	
Sustained Sequential Reads / Writes		
Bandwidth ⁴	2.5-inch	1.8-inch
	200GB: Up to 550 / 230 MB/s	200GB: TBD
	400GB: Up to 550 / 400 MB/s	400GB: TBD
	480GB: Up to 550 / 440 MB/s	800GB: TBD
	800GB: Up to 540 / 520 MB/s	
	1.2TB: Up to 500 / 500 MB/s	
	1.6TB: Up to 540 / 500 MB/s	
4KB Reads / Writes		
Random I/O Operations per Second ³	2.5-inch	1.8-inch
	200GB: Up to 84,000 / 12,000 IOPS	200GB: TBD
	400GB: Up to 84,000 / 25,000 IOPS	400GB: TBD
	480GB: Up to 84,000 / 28,000 IOPS	800GB: TBD
	800GB: Up to 84,000 / 28,000 IOPS	
	1.2TB: Up to 84,000 / 28,000 IOPS	
1.6TB: Up to 84,000 / 27,000 IOPS		
Interface	SATA 6Gb/s, compatible with SATA 3Gb/s	
Form Factor, Height and Weight	2.5-inch Up to 7mm / up to 96 grams	1.8-inch Up to 5mm / up to 96 grams
Life Expectancy	2 million hours Mean Time Between Failures (MTBF)	
Lifetime Endurance ⁸	Up to 3 Drive Writes per Day, Up to 10.7 Petabyte written	
Power Consumption ⁵	Active: Up to 6.8W Typical	Idle: 600mW Typical
Operating Temperature	0° C to 70° C	
RoHS Compliance	Meets the requirements of European Union (EU) RoHS Compliance Directives	
Product Health Monitoring	Self-Monitoring, Analysis and Reporting Technology (S.M.A.R.T.) commands	
Product Ordering Information	To order, visit intel.com/ssd	

1. Based on the Intel® Solid-State Drive DC S3500 Series Product Specification.

2. Based on the Intel® Solid-State Drive DC S3610 Series Product Specification.

3. Device measured using IOMeter* with 4K Random Writes QD=32 across 100% span of the drive. Latency measured using write transfer size of 4KB (4,096 bytes) and queue depth set to 1.

4. Performance measured using IOMeter* with 128K (131,072 bytes) of transfer size with Queue Depth 32.

5. Based on 5 volt power supply, measured on highest capacity SSD, see product specification for specific SKU information.

6. J. Gold Associates White Paper, *Investing in Solid State Drive Offers Significant Cost Advantage*

7. All capacities and form factors will not be available at launch.

8. Based on JESD218 standard

System Configuration for all performance testing: Intel® Core™ i7-3960x on Intel® DX79SI desktop motherboard, BIOS Version 0537 – SIX7910J.86A.0537.2012.0723.1217 8GB DDR3 LSI 9265-8i, FW 3.190.25-1776, Intel® SSD DC S3610 FW G2010110

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

Performance tests and ratings are measured using specific computer systems and/or components and reflect the approximate performance of Intel products as measured by those tests. Any difference in system hardware or software design or configuration may affect actual performance. Buyers should consult other sources of information to evaluate the performance of systems or components they are considering purchasing. For more information on performance tests and on the performance of Intel products, go to: http://www.intel.com/performance/resources/benchmark_limitations.htm.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request. Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order. Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web site at www.intel.com.

*Other names and brands may be claimed as the property of others.

Copyright © 2015 Intel Corporation. All rights reserved. Intel, the Intel logo, and Intel Inside are trademarks of Intel Corporation in the U.S. and other countries.