
msi°

GeForce RTX™ 4080 16GB SUPRIM X





SPECIFICATIONS

Model Name	GeForce RTX™ 4080 16GB SUPRIM X
Graphics Processing Unit	NVIDIA® GeForce RTX™ 4080 16GB
Interface	PCI Express [®] Gen 4
Core Clocks	TBD
CUDA® CORES	9728 Units
Memory Speed	22.4 Gbps
Memory	16GB GDDR6X
Memory Bus	256-bit
Output	DisplayPort x 3 (v1.4a) HDMI [™] x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a)
HDCP Support	Y
Power consumption	TBD
Power connectors	16-pin x 1
Recommended PSU	850 W
Card Dimension (mm)	336 x 142 x 78 mm
Weight (Card / Package)	TBD
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS

1. DisplayPort

2. HDMI

FEATURES



TRI FROZR 3S

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.




Airflow Control

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



Zero Frozr





Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Nave Curved 3.0



Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.