

Delock PCI Express 4.0 x16 Card to 4 x SFF-8639 NVMe - Bifurcation - Low Profile Form Factor

Description

This PCI Express card by Delock expands the PC by **four SFF-8639 interfaces**. SSDs with e.g. U.2 interface can be connected to these ports.

PCIe Bifurcation

The card requires the PCIe bifurcation of the motherboard to split the PCIe signal in order to use multiple ports.



Note

Without PCIe bifurcation only the first SFF-8639 port of the card can be used.

Specification

- Connectors:
 - PCIe card:
 - 1 x PCI Express x16, V4.0
 - 2 x SFF-8654 8i female
 - Connection cables:
 - 1 x SFF-8654 8i male
 - 1 x Molex 4 pin power plug >
 - 2 x SFF-8639 female
- Data transfer rate up to 64 Gbps
- Supports NVM Express (NVMe)
- Bootable, ex UEFI version 2.3.1
- Supports S.M.A.R.T.
- Supports TRIM
- 4 x LED indicator
- Humidity: 15 ~ 90 %
- Operating temperature: 5 °C ~ 50 °C
- Storage temperature: -25 °C ~ 70 °C

System requirements

- Linux Kernel 4.6.4 or above
- Windows Server 2016
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC with one free PCI Express x16 / x32 slot

Package content

- PCI Express card
- Low profile bracket
- 2 x Cable SFF-8654 8i male to 2 x SFF-8639 receptacle, length ca. 80 cm
- User manual

Item no. 90077

EAN: 4043619900770

Country of origin: China

Package: Box

Images



General	
Function:	Bootable, ex UEFI 2.3.1
Supported operating system:	Linux Kernel 4.6.4 or above Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2016
LED indicator:	4 x
Interface	
Connector 1:	1 x PCI Express x16, V4.0
Connector 2:	4 x SFF-8639 female
connector 3:	2 x Molex 4 pin power plug