



Delock PCI Express Card > 1 x internal NVMe M.2 PCIe / 1 x internal SFF-8643 NVMe – Low Profile Form Factor

Description

This PCI Express card by Delock expands the PC by one M.2 slot. One M.2 module in 2280, 2260, 2242 or 2230 format can be connected. Furthermore e.g. one SSD with U.2 interface can be connected by using an optional cable. Only one interface can be used, if both are occupied only the M.2 slot can be used.



Specification

· Connector:

internal:

1 x 67 pin M.2 key M slot

1 x PCI Express x4, V3.0

1 x 36 pin SFF-8643 female

- · Interface: PCIe
- Supports M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based

on PCIe

- Maximum height of the components on the module: 1.35 mm application of double-sided assembled modules supported
- Bootable, from UEFI version 2.3.1 (M.2 slot)
- Maximum output current: 4 A
- Short circuit protection, over heating protection
- ESD protection up to 2 kV
- LED indicator
- Power supply via PCI Express
- Supports NVM Express (NVMe)

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux Kernel 3.2
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

Package content

- PCI Express card
- · Low profile bracket
- 3 x fixing screw
- User manual

Item No. 89517

EAN: 4043619895175

Country of origin: Taiwan, Republic of

China


Package: Box



Images













| General | |
|-------------------------------------|--|
| function: | bootable |
| Supported operating system: | Linux Kernel 3.2 |
| | Windows 7 32-bit |
| | Windows 7 64-bit |
| | Windows 8.1 32-bit |
| | Windows 8.1 64-bit |
| | Windows 10 32-bit |
| | Windows 10 64-bit |
| LED indicator: | power and activity |
| Slot: | PCle |
| Supported module: | M.2 modules in format 2280, 2260, 2242 and 2230 with key M or key B+M based on PCIe $$ |
| Maximum height of the components on | 1.35 mm application of double-sided assembled modules supported |
| the module: | |
| Interface | |
| Internal: | 1 x 67 pin M.2 key M slot |
| | 1 x PCI Express x4, V3.0 |
| | 1 x 36 pin SFF-8643 female |
| Technical characteristics | |
| Maximum current: | 4 A |
| Physical characteristics | |
| Slot bracket: | low profile |
| | standard |