

# ABUS 8MPx IP PoE Mini Dome Camera

Art. no. TVIP48511

Page 1 of 3



- PoE surveillance camera for indoor and outdoor use, ideally placed on the ceiling; small, powerful and versatile security camera with professional features; stores on microSD, recorder/NVR or NAS
- Transfer video data to the router/switch/recorder extremely reliably via Power over Ethernet (PoE) with just one cable and keep the camera connected to power at the same time; optional power supply via 12 V DC plug-in power supply unit
- Lean start-up in just a few minutes using a PC/browser or recorder/monitor and free ABUS IP Installer (searches for IP address of camera in home or company network)
- Fully automatic object recognition of person and vehicle, ignores interfering influences such as branches or light, in vid. Configuration via established user interface with schedules, privacy zones, etc.
- True WDR function (120 dB) for backlit situations, IR LEDs for night vision up to 30 metres (depending on location), wind & weatherproof (protection class IP67, IK10), 4K resolution (Ultra HD, 8 megapixels) and 107° viewing angle
- Compact dimensions/size (mini dome design, diameter 11 cm) ideal for discreet 24/7 video surveillance in the company or at home; motion detection means less storage space is required and users can quickly find the scenes they are looking for
- Records via microSD memory card (accessory), network video recorder (NVR) or NAS (Network Attached Storage); H.265 Plus video compression for longer recording with ultra-efficient storage space utilisation
- Easy mobile access to live stream and memory with smartphone/tablet via the ABUS Link Station app, incl. push notification when motion alarm is triggered (with no additional settings required on the router); option to get info/images via e-mail/FTP

Mini dome camera with powerful functions Save time connecting. Discreet, reliable and clever monitoring. Save data. Cost-saving PoE technology For company premises, business, office or home: The 8MPx IP PoE Mini Dome camera is ideal for indoor/outdoor use and discreet monitoring from the wall. Power can be supplied via network cable, e.g. router or recorder (Power over Ethernet, PoE) - esp. useful in hard-to-reach spots, saving installation costs. Efficient start-up & clever video surveillance The surveillance camera differentiates fully automatically between person and vehicle - it only stores and reports what interests users. This and the strong data compression ensure highly efficient storage (recorder, NAS or microSD card). Even start-up is brief: Camera's user

# ABUS 8MPx IP PoE Mini Dome Camera

Art. no. TVIP48511

Page 2 of 3

---

interface is quickly accessed from a PC/browser or recorder/monitor and ABUS IP Installer and displays the first live image within minutes. Settings can also be customised quickly (e.g. schedules, privacy zones, etc.). Powerful WDR function & IR LEDs for consistently sharp imagesThe IP camera also manages heavily fluctuating light conditions, e.g. strong backlight in entries or outdoors in general (WDR 120 dB). It also has infrared LEDs for good visibility in the dark/at night. Mobile app accessUsers receive a push notification from the ABUS Link Station app in the event of a motion alarm. App's Pro version offers unlimited mobile access. Free with Lite version: up to 60 mins/month data stream (live view/playback).

# ABUS 8MPx IP PoE Mini Dome Camera

Art. no. TVIP48511

Page 3 of 3

## Technical Data:

Protection class IK	10
Image enhancement	WDR, BLC, HLC, 3D DNR, Vertical Display (only in surv. mode - no VCA)
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection
Technology	Network
Design	Dome
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Vertical viewing angle	57 °
Dimensions	(LxWxH) 109x109x85 mm
Alarming	Push-To-App, E-Mail, FTP, microSD
Number of users	32
Resolution	8 MP
Resolution modes	Stream 1: 3840 x 2160 @ 20 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1920 x 1080 @ 10 fps
Image sensor	1/2.8" Progressive Scan CMOS
Focal length	2,8 mm
Gross weight	0,47 kg
Dynamic range (WDR)	120 dB
Housing material	Metal
Horizontal viewing angle	107 °
IR LEDs	Yes
IR range (up to)	30 m
Power consumption	5 W
Max. resolution @ frame rate	3840 x 2160 @ 20 fps
Max. operating temperature	60 °C

Max. humidity	95 %
Microphone	No
Min. operating temperature	-25 °C
Minimum illumination (colour)	0,005 lx
Minimum illumination (IR)	0 lx
Net weight	0,55 kg
Lens mount	M12
PoE standard	IEEE 802.3af
Private zones	4
Noise reduction	3D DNR
IP protection class	67
DC voltage supply	12 (+/-25 %) V
Storage medium	microSD card, 256 GB (opt.)
OSD language	DE, UK, FR, NL, DK, IT
Day/night switching	ICR/Color/B/W
Supported browsers	Edge, Mozilla Firefox, Google Chrome
Encryption	HTTPS, TLS 1.1/1.2
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265
White balance	AWB, Manual