

# Delock Professional USB Condenser Microphone 24 Bit / 192 kHz for PC and Laptop

## Description

This professional USB condenser microphone by Delock can be used for high-quality voice and vocal recording, making it suitable for streaming, podcasting, gaming and video meetings.

### Optimal recordings

The microphone has a **16 mm condenser** and a **cardioid polar pattern (unidirectional)** and therefore ideally captures the sound. Due to high power, low self-noise and precise performance, even the finest sounds are recorded crystal clear.

### High resolution sampling rate

Typical USB microphones work with 16 Bit and 44 KHz. The Delock microphone offers a sampling rate of **24 Bit** and **192 kHz**, so it is possible to record in **Hi-Fi studio quality**.

### Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as **Windows, Mac OS, Chrome OS and Linux**.

### Stable & non-slip stand

The metal base with rubber feet ensures that the microphone stands stable on the table. The tripod table stand can be folded and transported easily if required.



## Specification

- Connector: 1 x USB 2.0 Type-B female
- Directivity: unidirectional
- Sensitivity: -38 dB +/- 3 dB
- Frequency range: 30 Hz - 16 kHz
- Sample rate: 24 Bit / 192 kHz
- Signal-to-noise ratio (SNR): ca. 70 dB
- Self-Noise: max. 16 dBA
- Sound pressure level (SPL): max. 120 dB
- USB bus powered
- Plug & Play

## System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

## Package content

- USB microphone
- USB 2.0 Type-A to USB 2.0 Type-B cable, length ca. 2.5 m
- Table stand (tripod)
- Microphone installation ring
- Windscreen
- User manual

## Item no. 66882

EAN: 4043619668823

Country of origin: China

Package: Retail Box

Images



General	
Function:	Plug & Play
Specification:	USB 2.0
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
Interface	
connector:	1 x USB 2.0 Type-A male 1 x USB 2.0 Type-B female
Input:	1 x USB 2.0 Type-B female
Technical characteristics	
Frequency range:	30 Hz - 16 kHz
Voltage:	USB bus powered
Sensibility:	-38 dB +/- 3 dB
Sample rate:	24 Bit / 192 kHz
Signal noise ratio (SNR):	ca. 70 dB
Directivity:	uni-directional
Physical characteristics	
Cable length:	2.5 m
Colour:	black